

## Accurate™ Freeze GR III FSC®

Description	Standard	Unit	Values											
			340	370	<b>400*</b>	440	<b>460*</b>	<b>490*</b>	<b>520*</b>	560	615	670	725	780
Thickness	EN 20534	microns (µm)	340	370	<b>400*</b>	440	<b>460*</b>	<b>490*</b>	<b>520*</b>	560	615	670	725	780
Weight	ISO 536	gsm (g/m <sup>2</sup> )	215	230	<b>245</b>	265	<b>275</b>	<b>290</b>	<b>305</b>	325	350	375	400	425
Stiffness Taber 15° MD	DIN 53121	mNm	7.7	9.8	<b>11.9</b>	15.0	<b>16.7</b>	<b>19.7</b>	<b>22.7</b>	27.4	34.1	41.9	50.8	60.8
Stiffness Taber 15° CD	DIN 53121	mNm	3.6	4.9	<b>6.0</b>	7.6	<b>8.5</b>	<b>10.0</b>	<b>11.6</b>	14.1	17.6	21.6	26.3	31.4
Brightness top	ISO 2470-2	% Elrepho	90											
Recyclability	EN 13430		in terms of the norm											
Biodegradability	EN 13432		in terms of the norm											

\* EBB stocked items

### Product Certifications

FSC  
Halal  
Food Safe

### Mill Certifications

ISO 9001  
ISO 14001  
ISO 50001  
ISO 22000