## **PRODUCT DATA**



# FASSON® MC Matt DI-OF FSC® Certified

Issued December 2023

## Introduction

Qualified self-adhesive material for INDIGO DIGITAL presses. Optimized to secure excellent runability and print performance.

**Description** 

Face: Premium-quality machine-coated woodfree paper, matt finish, white.

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

Availability

Adhesive Permanent

Backing **U** 

Crack-Back® Plus (diagonal cracklines)

## **Printing & Conversion**

This product is specifically engineered for use on the INDIGO DIGITAL sheet-fed press. The face material gives good toner key (no pre-treatment needed). Stable construction ensures problem-free runability. Before applying the label, the surface must be clean, dry and grease-free. Also printable in conventional offset.

**Features:** Qualified material ensures problem free conversion.

The unique Crack-Back® Plus: backing removal system with diagonal scored lines facilitates creating lay-outs, conversion and application of the

label.

## **Recommendations for use**

Multi-colour quality labels, promotional and collectable stickers using the advantages of full-colour DIGITAL printing such as: short runs, personalization etc. For indoor use.

#### General

Shelf life: 2 years stored at 20°C / 55% R.H.

Total caliper (±10 %): 177 micron

For information regarding EHS regulation, please visit our website under downloads "Technical bulletins" TB 7.8 Product Compliance Fasson Offset" and for technical guidance "Technical bulletins" – Offset printing.



## FASSON® MC Matt DI-OF FSC® Certified

## **PRODUCT CHARACTERISTICS**

## **Physical properties**

#### **Face**

#### **Adhesive**

Permanent: General-purpose water-based permanent adhesive with a high initial tack and

high adhesion on most common substrates.

Permanent

Adhesion (N/m)
(FTM 2 on steel/20 min. bond time)

Tack (N)
(FTM 9 on st.steel)

Minimum application temperature

+5

Service temperature range
after 24 hrs (°C)

Resistance to cold (°C) 1) down to

-20

#### **Backing**

Crack-Back® Plus: One-side-coated bleached kraft paper, with diagonally crush-scored lines, along

which the backing will crack cleanly when bent back, allowing easy removal in just two pieces. Lines are spaced just 32 mm apart. Good layflatness ensures

first-class printing and finishing.

(For optimal functionality take care of the following: minimum label size must be 20 cm<sup>2</sup>. The shortest side of a rectangle or the smallest diameter of an ellipse

must be at least 25 mm.)

Basis weight: 86 g/m<sup>2</sup> ISO 536

Caliper: 87 micron ISO 534

This product, FSC® C011032 certified, is sold as FSC® Mix Credit.

#### Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.

All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see https://www.lecta.com/terms
Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.



<sup>1)</sup> Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.