

PRODUCT DATA

FASSON®

FASSON® White PP Gloss DI-OF

Issued December 2023

Introduction

Authorized self-adhesive material for INDIGO DIGITAL presses. Optimised to secure good runability and print performance.

Description

Face: A white polypropylene film, glossy finish.

Availability	Adhesive ➡	Permanent	Removable
Backing ⤴			
No cracklines		x	x

Printing & Conversion

This product is specifically engineered for use on the INDIGO DIGITAL sheet-fed press

The face material gives excellent toner key (no pre-treatment needed).

Stable construction ensures problem-free runability.

Before applying the label, the surface must be clean, dry and grease-free. (see Technical bulletin 7.1)

Features:

100% ink transfer from blanket to paper to avoid.
Excellent ink bonding to avoid damage with scratching
Excellent layflatness for safe runability,
feed, delivery and kiss cutting

Recommendations for use

Multi-colour quality labels, promotional and collectable stickers using the advantages of full-colour DIGITAL printing such as: short runs, personalisation etc.

For indoor and outdoor use.

General

Shelf life: 2 years stored at 20°C / 55% R.H.

Total caliper (±10 %): 189 micron

For information regarding EHS regulation, please visit our website under downloads “Technical bulletins“ TB 7.8 Product Compliance Fasson Offset” and for technical guidance “Technical bulletins“ – Offset printing.

PRODUCT CHARACTERISTICS

Physical properties

Face

Basis weight:	43 g/m ²	ISO 536
Caliper:	59 micron	ISO 534
Tensile:	13 kN/m MD	ISO 1924/2
Opacity:	80 %	ISO 2471

Adhesive

Permanent:	General use acrylic permanent adhesive including smooth and slightly rough or curved surfaces.
Removable:	A glass-clear, acrylic-based adhesive for maximum sunlight and weather resistance. Good initial tack and ultimate adhesion. Resists high temperatures. Caution: Removability can be inhibited if the label is applied to surfaces with which it could react, such as surfaces with nitrocellulose-based paints, ABS, polystyrene, (fresh) screenprinting inks and certain types of PVC.

	Permanent	Removable
Adhesion (N/m) (FTM 2 on steel/20 min. bond time)	616	220
Tack (N) (FTM 9 on glass)	10.3	6.5
Minimum application temperature	+ 5	> +2
Service temperature range up to 24 hrs (°C)	+80	+90
up to 1 hr (°C)	+100	+100
Resistance to cold (°C) ¹⁾ down to	-20	-40

¹⁾ Not fully resistant until after adhesion reaches full strength – after at least 24 hrs.

Backing

No cracklines:	A one-side coated white kraft, featuring minimal moisture sensitivity.	
Basis weight:	120 g/m ²	ISO 536
Caliper:	118 micron	ISO 534

Guarantee and liability:

All product statements, technical information and recommendations are based on tests believed to be reliable but do not constitute a guarantee or warranty. Products are sold with the understanding that purchaser has independently determined the suitability of such products for its purposes.
All products are sold subject to Torraspapel – Lecta's general terms and conditions of sale, see <https://www.lecta.com/terms>
Fasson® and Crack-Back® are registered trademarks of Avery Dennison Corporation and related entities, and the products are produced by Torraspapel - Lecta under license from Avery Dennison Corporation and related entities for EMENA only.